



## **Minivans, Mini SUV's, Mini Trucks Demo Derby General Rules**

Must have long sleeve shirt, jeans, closed toed shoes, and full-face helmet. Eye protection required. (goggles, safety glasses, face shield)

All cars must be stock unless modifications are stated in the rules

Absolutely NO 4x4!! If vehicle is 4x4, 1 drive shaft must be removed

Any 4 or 6 cylinder allowed, v8 is allowed only if it came factory in vehicle

No welding anywhere unless specified

All glass, plastic, spare tires/parts, and interior must be removed! Dash may stay in. Passenger seat may stay if used to hold battery

All suspension must remain stock unless noted

Hood must have 10x10 hole cut out

Battery must be relocated to inside of the vehicle, and covered

Fuel cells are highly recommended, however gas tanks in front of rear axle may stay in stock location for fwd's only. If running rear wheel drive vehicle factory tank must be removed and fuel cell or factory tank must be moved to interior

Any wheel or tire is allowed

Aftermarket headers, shifters, and pedals are allowed

Unlimited 9-wire

Minimum of factory seat belt required, 4 or 5 point harness allowed

**AIR BAGS MUST BE REMOVED!!**

12"x12" roof sign is **REQUIRED!**

All vehicles must have working brakes!!

All trailer hitches and braces must be removed

You're allowed 1 fire, 2 your done!

**NO drivers door hits allowed!**

NO sandbagging or holding!

Drivers must be 18 years of age. Ages 16 and 17 must be accompanied by a parent or guardian

Interior

4 point cage and halo is allowed. Must have a minimum of a bar behind drivers seat. Floating cage only, no down bars

Fuel cell protector can be no bigger than 28"x28", may only be attached to the back seat bar

Transmission coolers are allowed

Exterior

Drivers door may be welded solid. All other doors are allowed unlimited 9-wire or chained

Body creasing is allowed. Truck beds must remain in the stock up right position

Suspension

Must remain stock. May use a 2"x6" flat steel to set ride height. Struts may be welded or clamped

Factory leaf springs only. NO stacked leafs!

Frames, Bumpers, Core Support

Any factory bumper is allowed. May be loaded and seam welded. Homemade bumpers are allowed, pointy bumpers can't measure more than 10" from the front to the back

8" bumper shocks may be used to attach bumpers. Maximum thickness of  $\frac{3}{8}$  and as tall as frame

NO core support spacers

1" threaded rod through the core support to hold the hood down, threaded rod may replace front subframe mount

May use  $\frac{1}{4}$  3"x3" 8" long inside frame rail instead of plate on outside of frame

Allowed 6 total repair plates, no bigger than  $\frac{1}{4}$  4"x6". MUST show proof of bend or break

**Any questions message us or call  
Dalton Haverkamp 319-239-8166**