



## Compact Car Demo Derby

### General Rules

Must have long sleeve shirt, jeans, closed toed shoes, and full face helmet. Eye protection required. (goggles, safety glasses, face shield)

Absolutely no rwd cars allowed!!

All cars must be stock unless modifications are stated in the rules

No welding anywhere unless specified

All glass, plastic, spare tires/parts, and interior must be removed! Dash may stay in. Passenger seat may stay if used to hold battery

All suspension must remain stock unless noted

Hood must have 10x10 hole cut out

Battery must be relocated to inside of the vehicle, and covered

Fuel cells are highly recommended, however gas tanks in front of rear axle may stay in stock location

Any wheel or tire is allowed

Aftermarket headers, shifters, and pedals are allowed

Unlimited 9-wire

Minimum of factory seat belt required, 4 or 5 point harness allowed

**AIR BAGS MUST BE REMOVED!!**

12"x12" roof sign is **REQUIRED!**

All vehicles must have working brakes!!

All trailer hitches and braces must be removed

You're allowed 1 fire, 2 your done!

4 cylinder and 6 cylinder **ONLY!!**

**NO** drivers door hits allowed!

**NO** sandbagging or holding

Drivers must be 18 years of age. Ages 16 & 17 must be accompanied by a parent or guardian

## **Cage**

4 point cage is allowed, minimum of rear seat bar. No down bars per side allowed.

Cage can't touch fire wall

Tank protector allowed but cant be within 3" of rear speaker deck

Aftermarket steering column is allowed

## **Drive Train**

Carb conversions are ALLOWED

Carb protectors are allowed, but can not strengthen the car in anyway

Transmission coolers are allowed

Radiators must be in stock location

Front motor mounts can be replaced with 2"x2" square tubing

NO swapping of motors. 4 cylinder must remain 4 cylinder and 6 cylinder must remain 6 cylinder

Reinforced or aftermarket tie rods are allowed

No full cradles

Aftermarket headers are allowed

## **Body**

Doors can be welded 5 on 5 off

Creasing is allowed

10"x10" hole cut in hood and trunk

NO welding seams anywhere

## **Suspension**

NO homemade or reinforced struts

Struts can be clamped or welded for ride height

## **Frame, Bumper**

Any car bumper may be used

Homemade bumpers are allowed. Maximum of 10" from back of bumper to point

Bumpers can be seam welded and loaded

Rear bumper must remain stock or removed

8" bumper shocks allowed. Maximum of  $\frac{3}{8}$ " and as tall as frame, if not plating outside of the frame you're allowed  $\frac{1}{4}$ " 3"x3" 8" long into the frame. This tube can be welded to the bumper

Two front cradle mounts may be removed and you may use 1" threaded rod to bolt solid

NO seam welding allowed anywhere

6 patch plates are allowed no bigger than  $\frac{1}{4}$ " 4"x6". Must show proof of bend or break

You may 9-wire subframe to body

Crush boxes can be cut out

**Any questions message us or call  
Dalton Haverkamp 319-239-8166**