

Mini Madness

- 1) Must have a minimum of three bars or mesh screening in front of the driver.
- 2) Window net is optional.
- 3) Racing seat is allowed but not mandatory.
- 4) Fuel cell must be securely mounted and covered in the rear of the vehicle. Stock tank must be in front of the rear axle to be kept in its original place. If behind rear axle it must be relocated in front of rear axle. If utilizing a plastic boat tank, it must be placed in a metal box. No 5-gallon gas cans allowed.
- 5) Any car leaking gas will be disqualified.
- 6) All seats, door paneling, carpet, headliner, and air bags must be removed. All glass from windows must be vacuumed and cleared out of the vehicle. Airbags need to be taken out- not just unhooked.
- 7) 4- or 6-point roll cage welded to the floor is allowed. Must have a minimum of a 2- point halo X- braced or must be attached firmly to the door post and roof.
- 8) No kickers from front dash bar to frame. bumper covers removed
- 9) Cage must not extend past the front firewall.
- 10) Battery and fuel cell must be covered.
- 11) Passenger seat must be removed unless it is holding the battery in place.
- 12) Battery must be moved to the interior of the vehicle. May secure in passenger seat or utilize plastic or metal homemade battery box if secured to the floor or roll cage.
- 13) No loose objects allowed to be in vehicles. All cans, garbage, tires must be removed before coming through inspection. If not you will need to go back and clean then come back through inspection
- 14) Almost any wheel/tire allowed. Solid tires are not allowed.
- 15) Tires can be foam filled, doubled, or tubed/liquid filled.
- 16) Vehicles can be run with the factory motor that came with them, no swapping motors. If it came with a V8 it can be run.

- 17) FWD OR RWD only. If vehicle has AWD or 4WD one drive shaft must be removed otherwise it will not be allowed to run.
- 18) Superchargers & turbos can be run but must be factory only. No aftermarket parts allowed with the exception of the cold air intake.
- 19) All frames must remain stock unless noted.
- 20) Total of 4 repair plates will be allowed sizing as follows: 4" X 6" X 1/4 "
- 21) Bend or break must be visible.
- 22) Any bumper may be used. Homemade bumpers allowed. Bumpers may be seam welded and loaded. Maximum of 5" point from rear of bumper to the tip of point. Must be not wider than vehicle
- 23) Bumper may have 2 straps welded to the core support. Chain & number 9 wire also acceptable.
- 24) Can use 3" X 3" X 3/8" square tubing to stuff in the crush box to attach the bumper.
- 25) Can build a steel support to protect the radiator. It cannot be any wider than the front frame rails.
- 26) No added metal to the body of the car unless noted.
- 27) May cap bumpers to the body using 14-gauge steel.
- 28) Rust repair must stay in place, no cutting out to remove. 14-gauge steel can be used to repair rust spots.
- 29) Hoods must be removable for inspection and in the event of a fire.
- 30) Must have 10 X 10 hole cut in hood
- 31) May weld or bolt a rub rail to the driver's door for extra protection. No pointy edges.
- 32) Doors must have a chain or wire holding them shut. Doors can also be welded shut.
- 33) All windows, headlights, and taillights need to be removed.
- 34) No sharp edges

